



PROCOMP

Stereo/ Dual Mono Programmable Effects Processor



FEATURES:

- Two independent compressor/limiter gates
- Stereo-linked or dual-mono operation
- Detector loop on each channel for side chain processing
- Balanced or unbalanced operation for both inputs and outputs
- Soft and hard knee compression for greatest flexibility
- Bypass switch for each channel
- Input and output level LED monitors
- Limiter/compressor selector on each channel
- Gate has threshold and release controls as well as threshold LED
- Gain reduction LED display for each channel
- All steel enclosure



SPECIFICATIONS:

Frequency Response

10Hz to 40kHz +/- 0.5dB

Input impedance

20K ohms

(balanced)

Maximum input level

+21dBu

Output impedance (balanced)

600 ohms

Output impedance (unbalanced)

300 ohms

Maximum output level (balanced)

+27dBu

Maximum output level (unbalanced)

+21dBu

Distortion

<.009% @ 1KHz typical

<.03%, 20Hz to 20KHz

Noise

-97dBu @ unity gain

-108 dBu @ gate on

(independent of output level)

-101dBu equivalent input noise

Dynamic range

117dB unweighted

>120dB "A" weighted

Crosstalk

<-85dB @1KHz

Wharfedale operate a policy of continuous product improvement and therefore reserve the right to change specifications without notice.

Wharfedale Professional, Sovereign Court, Ermine Business Park, Huntingdon, PE29 6XU, UK

Tel: +44 1480 447700 Fax: +44 1480 431767 Email: sales@wharfedalepro.com

www.wharfedalepro.com www.maxlight.ru Wharfedale is a Member of the International Audio Group (IAG)

